

GENIUS IP65




1000 lm IN SOLI 24 mm DI DIAMETRO.
FACILE MANUTENZIONE.

Genius IP65 è un incasso a scomparsa totale da esterni per installazione in soffitto di cartongesso o laterizio. La presenza di una lente protettiva IP65 satinata sulla sorgente luminosa e la sua combinazione con il corpo in Coral WaterOut®, lo rendono un prodotto resistente sia all'acqua che alla polvere. Con la versione per esterni la luce di Genius da oggi non ha più limiti ed è in grado di imporsi, discreto, in tutte le tipologie di ambiente. La parte elettrica è estraibile direttamente dal foro luce con un semplice gesto della mano, grazie alla meccanica push-pull, che facilita l'eventuale estrazione e la sostituzione della sorgente LED in caso di manutenzione.

1000 lm IN A DIAMETER OF JUST 24 mm,
EASY MAINTENANCE.

Genius IP65 is a total recessed outdoor luminaire installable on plasterboard or brick ceilings. The protective IP65 satin lens on the light source, perfectly merges with the Coral WaterOut® body, making the product resistant to both dust and water. With the outdoor version, Genius' light knows no limits and can now discreetly impose itself in any kinds of environments. The electrical part can be extracted directly from the emission hole with a simple hand gesture. This is possible thanks to the push-pull mechanism, which facilitates the eventual extraction and replacing of the LED source in case of maintenance.



TECHNICAL FEATURES

Code	1951.CW	1952.CW
Type	Downlight 90° ▲	Downlight 90° ▲
Material	CW: Coral WaterOut® waterproof	CW: Coral WaterOut® waterproof
Weight	0.8 Kg	0.8 Kg
Mounting	Ceiling recessed	Ceiling recessed
IP rating	IP65	IP65
Insulation class	III	III
Control gear	Remote constant current electronic driver (not included)	Remote constant current electronic driver and inverter
Cut out for plasterboard	135 x 110 mm	135 x 110 mm
Lamp type	LED 700 mA ⚡ V _f : 11.5 VDC	LED 700 mA ⚡
Lamp wattage	1 x 8.5W	1 x 8.5W
Luminous efficacy	1000 lm - 3000K	1000 lm - 3000K
Light distribution	Wide beam 40°	Wide beam 40°
Fitting	-	-
Light colour	White 3000K White 2700K 4000K (on request)	White 3000K White 2700K 4000K (on request)
Light hole	Ø 24 mm	Ø 24 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz
CRI	>90	>90
Emergency	-	1 hour
Energy efficiency class	A++	A++
Note	On request available dimmable PUSH or DALI, remote installation.	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1951.CW	H8700.E	Constant current electronic driver. Remote installation	Suitable for n°1 or n°3 code 1951.CW - 700 mA
	BR1951LT	Brick box	Dimensions L: 195 mm; W: 140 mm; D: 160 mm (instructions on page 502)
1952.CW	BR1952LT	Brick box	Dimensions L: 195 mm; W: 140 mm; D: 160 mm (instructions on page 502)



Private villa - Austria